Enviro Systems Inc Quality Clauses

Green indicates changes for Rev M--- Section 100 added: Suppliers, including sub tier suppliers, shall have a system for notifying Enviro if a determination is made that suspect Non-conforming product (NPC) has been released. This notification must occur within 24 hours (excluding weekends and holidays) of its discovery.

Yellow indicate changes for Rev P - QC Clause 353 added "and or identified by Ace Thermal Systems"

Peach indicates changes for Rev Q - Added QC Clause 400, 4/1/2023

CERTIFICATE OF CONFORMITY	
1	CERTIFICATE OF CONFORMANCE-STANDARD On Production Materials with a Purchase Order, a Supplier Certificate of Conformance (COFC) is required on each shipment. It must indicate PO number, Enviro part number, revision level, quantity, and applicable specifications. Supplier confirms and guarantees that all parts delivered are newly manufactured and meet all specifications and requirements specified in the purchase order or in referenced documents.
	CERTIFICATE OF CONFORMANCE-SPECIAL PROCESS FOR ENVIRO DRAWINGS ONLY
2	A Supplier Certificate of Conformance (COFC) is required on each shipment & must indicate PO number, Enviro part number, revision level, quantity, welding specification, plating or finish as per drawing and/or required specifications. The plating, finish (alodine, anodize, electropolish, paint, or nitride), heat treat, or weld specification must note the revision level of the specification. If the special process is <u>out-sourced</u> , the special process source must be approved in advance by Enviro and the sub-tier COFC must accompany the suppliers COFC. Special processes that are <u>in-sourced</u> , also, must be approved in advance by Enviro.
	CERTIFICATE OF CONFORMANCE-FLAMMABILITY
3	Certification of Conformance to applicable flammability requirements of FAR's shall accompany each shipment. Burn test Data required with shipment.
	CERTIFICATE OF CONFORMANCE-FABRICATED PRODUCTS
4	A Supplier Certificate of Conformance (COFC) is required on each shipment & must indicate PO number, Enviro part number, revision level, quantity, welding specification, pressure test requirements, plating or finish as per drawing and/or required specifications. If any raw material is specified on the Enviro Drawing a certification is required, and the lot or batch number of the raw material is to be included on the COFC; this provides written linkage between the raw material certification and the fabricated part.
	CERTIFICATE OF COMPLIANCE-METALLIC RAW MATERIAL CERTIFICATION
5	Material Certificate of Conformance (COFC), Mill Certificate or Inspection Certificate for raw material analysis is required with shipment. Certificate shall include: part identification, required specification, chemical analysis, mechanical properties, heat/lot identification and/or any other required specifications as applicable. Material certifications must agree in all respects with the raw material requirements of their applicable specifications. The certifications shall contain a statement signed by an authorized quality representative that the items provided meet the Enviro System, Inc requirements, list the purchase order and the Enviro part numberIn the event Enviro receives material without Mill test Reports, supplier agrees to fax reports within 24 hours from being notified. Material must be labeled with the P.O. number and Enviro part number.
	CERTIFICATE OF COMPLIANCE- CALIBRATION
6	The supplier shall provide certification of calibration that indicates traceability to the National Institute of Science and Technology (NIST) per ANSI / NCSL Z540-1. Equipment used for calibration is referenced in the COFC with standard nomenclature, serial number, NIST report number and calibration date. The certificate shall include the Enviro Systems, Inc. purchase order number and environmental conditions at time of calibration. Out of tolerance conditions shall also be denoted. The Quality Manager or Designee of the supplier shall sign the certificate.

7	CERTIFICATE OF COMPLIANCE-BURN IN
	Parts to be screened by American Reliability per procedure listed in Alstom Spec GESI-267. Each shipment of parts to be accompanied by a Summary
	Report including Certificate of Compliance and Lot Traveler as defined in the applicable procedure, and a copy sent to Alstom Signaling, ATTN.:
	Standards, PO Box 20600, Rochester, NY 14602 or faxed to 585-783-2321.
8	FAA FORM 8130-3 CERTIFICATION RETURN FOR REPAIR OR OVERHAUL
	FAA form 8130-3 shall accompany parts that are being returned from the supplier for repair or overhaul.
	CERTIFICATE OF COMPLIANCE-CHEMICAL ANALYSIS AND PHYSICAL PROPERTIES
9	Products with this code must provide product manufacturer date, ship date, shelf life, if applicable and MSDS (material Safety Data Sheet) with each
	shipment.
40	CERTIFICATE OF COMPLIANCE-BMS10-83 BOEING TEST ACCEPTANCE
10	BMS10-83 Standard Boeing Test Acceptance and the AKZO Certification must be provided with actual test reports.
44	CERTIFICATE OF COMPLIANCE-SPEC D6-51377 REV E SEC.4.1B
11	COFC must state the material meets smoke and toxicity requirements of BOEING SPEC D6-51377 REV E SEC. 4.1B
	CERTIFICATE OF CONFORMANCE-HEAT TREAT
	Each chiamant shall be accompanied by a legible and reproducible convent to detailed heat treatment evels used. Details to include drawing
12	Each shipment shall be accompanied by a legible and reproducible copy of the detailed heat treatment cycle used. Details to include: drawing
	requirement, specification, date, time, temperature and quench method as applicable. Inspection reports must accompany the heat treat report. The
	report shall contain the signature and title of the authorized representative of the agency performing the tests and inspections.
	CERTIFICATE OF CONFORMANCE- MILL HEAT CONTROL/MILL CERTIFICATION/SERIALIZATION
13	Assigned serial numbers must be consecutive within a mill heat.
13	All items covered by this Purchase Order shall be from the same mill heat.
	Actual mill certification required.
	CERTIFICATE OF COMPLIANCE- CALIBRATION OF OEM EQUIPMENT
	The supplier shall provide certification of calibration that indicates the original equipment manufacturer has calibrated the equipment to the OEM
	standards traceable to NIST standards. Most equipment manufacturers lack certification to ANSI / NCSL Z540-1 as they are not calibration laboratories,
14	thus calibration to the OEM requirements by the OEM is acceptable. Equipment used for calibration is referenced in the COFC with standard
'7	nomenclature, serial number, NIST report number and calibration date. The certificate shall include the Enviro Systems, Inc. purchase order number and
	environmental conditions at time of calibration. Out of tolerance conditions shall also be denoted. The Quality Manager or Designee of the supplier
	shall sign the certificate.
	SHIPPING, PACKAGING AND DELIVERY
	SHIPPING INSTRUCTIONS- LABELING
	Parts (or packaging around each part) must be individually marked, tagged or labeled with the Purchase Order and Enviro Part Number. Small parts can
51	be packaged in appropriate containers, and each package must be labeled with the Purchase Order, Enviro Part Number and Quantity. Any labels
	attached directly to parts must be easily removed without leaving adhesive residue. This section does not apply to serialized parts which would have
	each part identified with a serial number.
	SHIPPING INSTRUCTIONS-PACKING PEANUTS OR LOOSE PACKING MATERIAL
52	No packing peanuts or any other loose packing material, such as shredded paper is allowed in shipping boxes.
	PACKAGING AND HANDLING-GENERAL REQUIREMENTS
	In performance of the contract, the supplier shall assure that all articles are packaged in a manner and with materials necessary to prevent deterioration,
53	corrosion or damage. Requirements for packaging shall consider conditions affecting the article while at the supplier's plant, transportation to
	destination and the expected conditions at the destination.
	The same and a same and a same accumum.

	NON CONFORMING
	SUPPLIER NON-CONFORMING MATERIALS
100	In the event a supplier has manufactured materials which are non-conforming to Enviro Systems purchase order requirements, supplier may request Enviro Systems Material Review of the non-conforming material(s) by submitting a Supplier Deviation Request Form (F06.01-08)citing the non-conforming condition and requesting Enviro's disposition and/or concurrence. The supplier may then complete the manufacturing cycle. Completed Supplier Deviation Request must accompany parts when shipped. Suppliers, including sub tier suppliers, shall have a system for notifying Enviro if a determination is made that suspect Non-conforming product, (NPC) has been released. This notification must occur within 24 hours (excluding weekends and holidays) of its discovery.
	ALL REWORK OF NON-CONFORMING MATERIALS MUST BE DOCUMENTED
101	A Non-Conforming Material Report (NMR) will accompany all returns to the supplier. Any suplier rework MUST be documented & a copy of the document MUST be sent with the return shipment. Enviro Systems, Inc. will perform an incoming inspection of the reworked components before acceptance of the shipment.
	CORRECTIVE ACTION
102	For a confirmed non-conforming complaint, the supplier agrees to perform 100% inspection of the non-conforming characteristic for the next three consecutive manufactured lots.
	CORRECTIVE ACTION
103	Supplier agrees to respond to the SCAR/SPAR in the time frame documented on the request, determine the root cause of the nonconformance, develop and implement plans of corrective action to prevent recurrence.
	FINAL INSPECTION
151	FINAL INSPECTION All items are subject to final inspection and acceptance upon receipt at Enviro Systems facility regardless of any prior inspection or test at supplier's facility
	TEST DATA
200	TEST DATA-SUBMITTAL OF TEST DATA The Supplier will supply with each lot of material shipped recorded functional test data. Such data shall apply to a normal sample, inspection level II, 1%
	AQL per MIL-STD-105E. Submitted data shall be traceable by serial number or other identification to the particular part(s) to which it applies.
201	TEST DATA-ACCEPTANCE TEST DATA Acceptance Test Data required with parts when received.
202	TEST DATA-ACCEPTANCE TEST DATA 100% functional testing is required for each shipment. COFC to indicate test was performed. For PCBs this applies only if test equipment is available and the drawing requires testing
203	TEST DATA-ADHESION TEST
	All preprocessed materials that are chemical filmed per MIL-C-5541 (Rev. E or higher) and primed per MIL-P-23377 (Rev. G or higher) which will have subsequent forming operations shall pass adhesion test per ASTM D522 Method A for flexibility and ASTM D2794 for impact at 60inch-pounds, using a 0.0625" diameter indenter with a minimum combined mass of the indenter and weight of 1045 grams. Prime thickness of production parts and test panels shall be between 0.4 – 0.9 mils. Three test articles of 2024 bare aluminum 0.032" thick shall be processed with each production run and tested for flexibility, adhesion, impact resistance and paint thickness. Questions concerning test should be directed to Enviro Systems, Inc. engineering.
204	TEST DATA-CONDUCTIVITY TEST FOR MIL-C-5441 CLASS 3 ALODINE Mil-DTD-81706 resistance testing data is to be supplied.

205	TEST DATA-SAMPLE COMPONENTS
	Sample components, such as coupons from castings, must be supplied in accordance with the notes on the drawing or purchase order.
	FIRST ARTICLE
	FIRST ARTICLE INSPECTION (FAI)
251	Supplier shall perform a first article inspection on a part from each first lot shipment to verify all engineering characteristics. First article inspection shall
	be recorded and shipped with parts.
	FIRST ARTICLE INSPECTION (FAI)
252	FAI report is required for each part number with the initial shipment to Enviro. FAI report shall include actual measured values of all dimensional and
	drawing note compliances for one sample part to support the drawing of C of C. Supplier FAI Form is acceptable.
	FIRST ARTICLE INSPECTION (FAI)
253	FAI report in accordance with AS-9102 is required for each part number with the initial shipment to Enviro. FAI report shall be on AS-9102 forms and
253	include actual measured values of all dimensional and drawing note compliances for one sample part to support the drawing C of C. A full dimensional
	layout report required for one (1) piece. To be delivered with shipment.
	PRODUCTION FIRST ARTICLE REPORTS
	Compliance to requirements shall be demonstrated by submitting a First Article Inspection Report with the first lot shipment of product and a delta FAI
	· · · · · · · · · · · · · · · · · · ·
	with the first lot shipment of each subsequent revision for those dimensions/conditions affected by the revision. Catalog parts are excluded; for catalog
	parts such as MS, NAS, AN, etc., A certificate of conformance to all purchase order requirements are required. First article inspection reports shall
	include serial numbers (when applicable), all dimensions, general notes, tolerance ranges, actual measurements and where physical testing is required,
254	the results of the tests. First article parts shall be identified as "First Article" by paper tagging or any other suitable means of identification. Enviro
254	Systems, Inc. recommends suppliers adopt AS9102 format as the foundation for their first article reporting.
	Additional first article inspection shall be performed when:
	· Either new manufacturing process or new methods are used that could affect compliance to the drawing requirements.
	· New, reworked or transferred tooling is in use.
	· A drawing revision affects the operation performed by the supplier.
	· A new supplier is contracted to manufacture the part.
	· As required by Enviro Systems, Inc.
	FIRST ARTICLE INSPECTION (FAI)
	Constitution of the description of the description of the first the first tendence of the description of the first tendence of tendence
	Compliance to requirements shall be demonstrated by submitting a First Article Inspection Report with the first lot shipment of product and a delta FAI
	with the first lot shipment of each subsequent revision for those dimensions/conditions affected by the revision. Catalog parts are excluded; for catalog
255	parts such as MS, NAS, AN, etc., A certificate of conformance to all purchase order requirements are required. First article inspection reports shall
	include serial numbers (when applicable), all dimensions, general notes, tolerance ranges, actual measurements and where physical testing is required,
	the results of the tests. First article parts shall be identified as "First Article" by paper tagging or any other suitable means of identification. Enviro
	Systems, Inc. recommends suppliers adopt AS9102 format as the foundation for their first article reporting.
	FIRST ARTICLE INSPECTION (FAI) FOR CIRCUIT BOARDS
•	

Ī	
	1. IPC 6012/IPC 610 for class 2 or 3 which ever print requires.
	2. Electrical Testing.
256	3. Bare board manufacturer Test Report.
	4. Impedance Reports. (If Applicable)
	5. 4. Micro section / Solderability Test Report.
	6. Final FAI Report from Supplier.
	7. Cleanliness Test report. (For Contamination)
	FLOW DOWN REQUIREMENTS
	FLOW DOWN-CONFIGURATION MANAGEMENT OF ENVIRO DRAWINGS
	Supplier shall notify Enviro's purchasing department: when engineering data in supplier's possession does not agree with the latest revision data
300	reflected on P.O., and when additional specifications/drawings not listed on P.O. but required by controlling engineering data are needed. Required
	drawings for supplier subtiers must maintain configuration management of Enviro Drawings
	FLOW DOWN-CONFIGURATION MANAGEMENT OF SPECIAL PROCESSES
	The plating, finish, heat treat or weld specification must be processed to the latest version of the specification noted in the purchase order or Enviro
301	Systems drawing. A list of specifications is located at www.enviro-OK.com on the Enviro Systems portal. The supplier of special processes is to review
	this document on the Enviro Systems portal and verify the specification used to produce the Enviro part aligns with the revision level documented on the
	Enviro Systems portal. This revision level must be noted on the COFC (See Quality Clause 2)
	FLOW DOWN-GOVERNMENT SOURCE INSPECTION
222	The Government has the right to inspect and test all supplies called for by contract, to the extent practicable, at all places and times, including the period
302	of manufacture, and in any event before acceptance. Government source inspection may be required at Supplier/subcontractor plant prior to shipment.
	Upon receipt of this order please furnish a copy of the purchase order to your local DCAS representative. The Supplier/subcontractor shipping document
	must bear government source inspection stamp if the requirement is imposed.
	MANUFACTURING CONTROL
303	A system shall be employed for controlling, documenting and maintaining product quality levels through out the manufacturing process. No process shall
	be changed that affects fit form and function without written authorization.
	UNAUTHORIZED FACILITY CHANGES
304	During performance of the purchase order, Supplier shall give buyer written notice before relocation of any Production, Inspection or Processing Facilities or
	making any other CHANGES that may affect product quality.
	UNAUTHORIZED PRODUCT CHANGES OR SUBSTITUTIONS
	Supplier shall not make any changes or substitutions of any products or services required by the applicable drawing, specification or document unless:
305	A. Any Major (or Class 1 changes) that affect form, fit or function always requires prior approval by Enviro Systems before implementing.
	B. Any change will require prior approval by Enviro Systems before implementing.
	C. Minor Changes (or Class 2 changes) require notification to Enviro Systems before shipment.
	MIL-STD-1686 ESD CONTROL REQUIREMENTS
306	Supplier shall comply with requirements set forth in MIL-STD-1686 and/or JEDEC 108 during storage, handling and shipment. ESD sensitive items shall
	have an ESD warning label, this should be used to seal shielded bags when applicable.
	PROTECTION OF ELECTOSTATIC SENSITIVE DEVICES
	TROTEGRAN OF ELECTORISTIC GENORITYE DEVICES

307	All voltage sensitive devices &/or sub-assemblies & assemblies containing such devices shall be protected from static electricity & transient voltage in
307	
	accordance with the requirements specified on the drawing or specification for which the devices are procured. SHELF LIFE-ELASTOMERS
308	Cure date, shelf life, and/or manufacture date required with material when received. Parts must have at least 85% shelf life remaining when Enviro
	· · · · · · · · · · · · · · · · · · ·
	receives shipment.
200	SHELF LIFE-CONSUMMABLES
309	Cure date, shelf life, and/or manufacture date required with material when received and have at least 85% shelf life remaining when Enviro receives
244	shipment.
311	NO 2000 OR 7000 SERIES ALUMINUM ALLOYS TO BE USED
	SUPPLIER RECORDS (ELEVEN YEARS)
312	Supplier shall retain all required records objectives evidence of conformance to the Purchase Order requirements. Required records including but are not
0.12	limited to Certificates of Conformance, inspection data, training records, nonconforming material disposition, test data, & process flow sheets. These
	record are to be retained for a minimum of eleven (11) years.
	SUB-TIER CONTROL
313	The supplier shall be responsible for flow down of all the requirements and provisions of the Enviro Systems, Inc. purchase order applicable to the
	supplier's sub-contractors.
	FACILITY ACCESS
	During the performance of any Enviro System, Inc. purchase order, the supplier's quality assurance or inspection and manufacturing process are subject
314	
	to review and analysis by Enviro Systems, Inc., our customer and/or government representative. This requirement is applicable to the supplier's facilities
	where Enviro Systems, Inc. products and services are processed as well as the supplier's sub-tier facilities.
	DOMESTIC MATERIAL
315	When specified by purchase order requirements or imposed by DFARS 252.225, all raw material incorporated into the delivered item must be
313	manufactured in the United States, its outlying territories or by specific qualifying countries as defined in the DFARS 252.225-7002. Stainless steels are
	covered under DFARS 252.225-7008 (Restriction on Acquisition of Specialty Metals)
	ELECTRONIC COMPONENT OBSOLESCENCE
317	Suppliers of electronic circuit boards are to notify Enviro Systems if any component used for Enviro assemblies is becoming obsolete. Immediate notice
	is critical for selecting substitute components or redesigning circuit boards.
	COUNTRY OF ORIGIN FOR METALLIC RAW MATERIALS
318	The metallic raw materials (plate, sheet, bar, rod, tube, etc) must be from a country that is listed in the FAA Bilateral Agreements in
	http://www.faa.gov/aircraft/air cert/international/bilateral agreements/baa basa listing
	FASTENER QUALITY ACT Public Law 101-592
319	Fasteners (6mm or 1/4" in diameter or larger) of high strength that are grade marked) must be provided in compliance with the FASTENER QUALITY ACT.
	The COFC must reflect compliance for any applicable fasteners.
	CHANGES TO DOCUMENTS
320	Corrections to work instructions or documents must be recorded, dated and signed (or initialled) in ink or other permanent marking method with the original data
	being legible and retrievable after the change.
	EYE EXAMINATIONS FOR INDIVIDUALS PERFORMING VISUAL INSPECTION
321	Supplier must verify annually that inspectors performing Visual Inspections are compliant with near vision requirements such as Snellen 14/18, (20/25),
	Jaegar 2 at 14 inches or Ortho-Rater 8
	VERBAL AGREEMENTS OR INSTRUCTIONS
İ	TENDAL MORELIMENTO ON INCOMOTORO

322	Supplier shall under no circumstances interpret verbal agreements or instructions as approval or authorization to proceed. Electronic or paper
	confirmation of verbal information is required.
323	Silver Plated Wire (MIL-W-22759 and MIL-W-168781)
	Purchased wire spools must be sealed on the ends, the spools must be plastic, and each spool is to be sealed in a clear plastic bag with desicant. Each spool must be labeled with "WARNING MOISTURE DAMAGES WIRE-KEEP ENDS SEALED" or equivalent warning.
324	Major or Minor (Class 1 or Class 2) Engineering Changes-Major Changes Require Approval Before Implementation, Minor Changes Require Notification Before Shipment.
	The Supplier shall notify Enviro Systems of any engineering change to the Product as soon as the Supplier determines a change is required. The notification shall be submitted to Enviro's purchasing department using Enviro's Supplier Change Control Form or other form as agreed to by Enviro. For Class 1 or Major changes, those changes that effect the products form, fit, function, reliability, weight or performance, the Supplier must receive Enviro written approval prior to implementing the change. For all other changes, the change notification must be submitted prior to shipment of 1 st product incorporating the change. If Enviro determines a change to be Class 1 or Major and it is not submitted as such, Enviro at its sole discretion can return the
	Products to the Supplier for credit. All Major or Minor (Class 1 or Class 2) Engineering Changes Require Approval Before Implementation
	All Major of Millor (Class 1 of Class 2) Engineering Changes Require Approval Before Implementation
325	The Supplier shall notify Enviro Systems of <u>any</u> engineering change to the Product as soon as the Supplier determines a change is required. The notification shall be submitted to Enviro's purchasing department using Enviro's Supplier Change Control Form or other form as agreed to by Enviro. The Supplier must receive Enviro written approval prior to implementing the change. If Supplier provides products that incorporate unapproved changes, Enviro at its sole discretion, can return the Products to the Supplier for credit.
	Changes on Catalog Items
326	A system shall be employed for controlling, documenting and maintaining product quality levels through out the manufacturing process. No process or drawing change which effects form, fit or function shall be changed without written notification to Enviro Systems, prior to shipment.
	Conflict Materials per Dodd-Frank Act
327	Enviro Systems requires that all suppliers do not knowingly use any conflict materials (tin, gold, tantalum, tungsten) originating from the Democratic Republic of the Congo (DRC) or the neighboring countries. This requirement must flow down to the suppliers sub-tier suppliers. The supplier will notify Enviro Systems immediately if the supplier gains knowledge that material was supplied to Enviro Systems containing Conflict Materials. The notification must include the purchase order number, the part number and any traceability data available to the supplier.
	NADCAP Requirements for Special Processes
328	For all parts coded 1100XXX-XX, all of the following special processes must be performed by a NADCAP certified company for the following processes that are defined in the Enviro drawing. The special processes where NADCAP certification applies are: Anodize per MIL-A-8625 Type II Class 2, Black Heat Treat per AMS 2759 Chemical Conversion Coat per MIL-DTL-5541 Type II Class 3 Zinc Nickel Plate per AMS2417 Type 1 Passivate per AMS 2700 Type 2 Passivate per SAE-AMS-QQ-P-35 Welding AWS D17.1
	TRACEABILITY
351	TRACEABILITY-PCB SERIAL NUMBERS PCB serial numbers shall be in accordance with the drawing or identified to the purchase order in a method so a unique serial number on the PCB board can be traced to a
	specific purchase order number.
352	TRACEABILITY-SERIAL NUMBERS Parts must be individually marked at tagged with Unique Social Number, not to be repeated for the life of the component.
	Parts must be individually marked or tagged with Unique Serial Number, not to be repeated for the life of the component.

353	COUNTERFEIT COMPONENTS
	All subcomponents of circuit boards and all subcomponents ordered individually must be purchased from the OEM, or a distributor that the OEM has authorized and or identified by Ace Thermal Systems which shall comply with the requirements of AS5553 for electronic components. All non-electronic products must be purchased from the OEM of the component or distributor that the OEM has authorized and products must comply with requirements of AS6174. Any components that are not from the OEM or their authorized distributor cannot be delivered without notice to Enviro Systems and approval by Enviro Systems in accordance with Quality Clause 100 SUPPLIER NON-CONFORMING MATERIALS
354	TRACEABILITY-GENERAL REQUIREMENTS
	Each subcomponent of an assembly must be traceable to the a defined lot of material. The material lot may consist of multiple purchase orders (for example if a work order of 50 pieces has a subcomponent and the 50 subcomponents came from two different purchase orders)
FOREIGN OBJECT DEBRIS (FOD)	
400	FOD
	Defined as any object, particle, substance, debris or agent that is not where it is supposed to be, and: In an aviation or similar environment, could create a hazard to aircraft, equipment, cargo, personnel or anything else of value is not permitted by any means.